- (21) Application No 9111096.5
- (22) Date of filing 23.05.1991
- (30) Priority data (31) 4016776

(32) 25.05.1990

(33) DE

(71) Applicant Mtu Motoren-Und Turbinen-Union Friedrichshafen

(incorporated in the Federal Republic of Germany)


Olgastrasse 75, Postfach 20-40, D-7990 Friedrichshafen 1, Federal Republic of Germany


- (72) Inventor Hans Sudmanns
- (74) Agent and/or Address for Service Boult Wade & Tennant 27 Furnival Street, London, EC4A 1PQ, United Kingdom


- (51) INT CL* F04D 27/00, F02B 37/12, F04D 25/00
- (52) UK CL (Edition K) F1C CBE CBF CD C114 C204 C505 C517 C521 C522 C602 F1B BBD BB120 BB140 F1G GPG U1S 61994
- (56) Documents cited GB 2179401 A GB 0540496 A GB 1343246 A GB 0576241 A DE 3932721 C
- (58) Field of search UK CL (Edition K) F1C CBA CBB CBC CBD CBE INT CL* F04D 25/00 25/02 25/04 25/16 27/00 Online databases : WPI.

(54) Turbocharging assembly with controllable air-charge compressors for an internal-combustion engine

(57) Air-change compressors (16, 17) are in permanent driving connection with an exhaust-driven turbine (15) which cannot be cut out during operating periods of the Internal-combustion engine. The control of the operating condition (no-load delivery or delivery operation) of each air-charge compressor (16, 17) is effected by a change-over device (20) controlling the pressure connection. To improve the efficiency of the turbocharging assembly (12) the power absorption of whichever air-charge compressor (16, 17) has just been adjusted to no-load delivery is minimised by controlling the fluid mass throughput of (for example) "recirculated" air or turbine exhaust gas (eg. Figs. 3, 4) through that compressor. Devices (29, 30) of the compressors (16, 17) enable the direction of air flow to the rotors to be controlled to impart one of counter-swiri, no-swirl or co-swirl to the air entering the rotor.










FIG. 4